

LL4120 | Ball valve with built-in filter and reducer left



Features	
Working pressure	16 bar (232 psi)
Working temperature	from 0°C to +120°C (from 32 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
<hr/>	
Size	F1/2"xF1/2"

LL4121 | Ball valve with built-in filter and reducer right



Features	
Working pressure	16 bar (232 psi)
Working temperature	from 0°C to +120°C (from 32 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
<hr/>	
Size	F1/2"xF1/2"

LL9045 | Adjustable anti-scald thermostatic mixing valve



Features	
Working pressure	16 bar (232 psi)
Regulated temperature range	from 38°C to +65°C (from 100 °F to 149 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
<hr/>	
Size	1/2"x1/2"x1/2" 3/4"x3/4"x3/4"

LL9046 | Adjustable anti-scald thermostatic mixing valve



Features	
Working pressure	16 bar (232 psi)
Regulated temperature range	from 38°C to +65°C (from 100 °F to 149 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
<hr/>	
Size	1/2"x1/2"x1/2" 3/4"x3/4"x3/4"



LL4111 | Pressure reducing valve



Features	
Working pressure	16 bar (232 psi)
Working temperature	from 0°C to +120°C (from 32 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
<hr/>	
Size	1/2" 3/4"

LL3095 | Pressure reducing valve



Features	
Working pressure	16 bar (232 psi)
Working temperature	from 0°C to +120°C (from 32 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
<hr/>	
Size	1/2" 3/4" 1" 1 1/4" 1 1/2" 2"

ACS ERL

LL4063 | Brass balancing valve



Features	
Working pressure	20 bar (290 psi)
Working temperature	from 0°C to +120°C (from 32 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
<hr/>	
Size	1/2" 3/4" 1" 1 1/4" 1 1/2" 2"

ERL

LL4063B | Brass balancing valve



Features	
Working pressure	20 bar (290 psi)
Working temperature	from 0°C to +120°C (from 32 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
<hr/>	
Size	1/2" 3/4" 1" 1 1/4" 1 1/2" 2"



LL3190 | Brass supply valve

NEW



Features	
Working pressure	16 bar (232 psi)
Working temperature	from -10°C to +80°C (from 14 °F to 176 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
<hr/>	
Size	1/2"

LL3189 | Brass diaphragm pressure reducing valve

NEW



Features	
Working pressure	16 bar (232 psi)
Working temperature	from -10°C to +80°C (from 14 °F to 176 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
<hr/>	
Size	1/2" 3/4" 1"

LL4108 | Differential pressure control valve



Features	
Working pressure	16 bar (232 psi)
Working temperature	from 0°C to +120°C (from 32 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
<hr/>	
Size	1/2" 3/4" 1" 1 1/4" 1 1/2" 2"