

## 1-Piece Instrumentation, 40G and 40 Series


**Part No.**

SS-43GXS4

**Part Description**

Stainless Steel 1-Piece 40GGG Series 3-Way Ball Valve, 0.90 Cv, 1/4 in. Swagelok Tube Fitting

## Specifications

### General

<b>Actuator Type</b>	Manual
<b>Ball/Stem Material</b>	Stainless Steel
<b>Body Material</b>	316 Stainless Steel
<b>Cleaning Process</b>	Standard Cleaning and Packaging (SC-10)
<b>Connection 1 Size</b>	1/4 in.
<b>Connection 1 Type</b>	Swagelok® Tube Fitting
<b>Connection 2 Size</b>	1/4 in.
<b>Connection 2 Type</b>	Swagelok® Tube Fitting
<b>Connection 3 Size</b>	1/4 in.
<b>Connection 3 Type</b>	Swagelok® Tube Fitting
<b>eClass (4.1)</b>	37010401
<b>eClass (5.1.4)</b>	37010401
<b>eClass (6.0)</b>	37010401
<b>eClass (6.1)</b>	37010401
<b>Flow Pattern</b>	3-Way, Switching
<b>Handle Color</b>	Black
<b>Handle Style</b>	Lever
<b>Lubricant</b>	Dow M111
<b>Max Temperature Pressure Rating</b>	300°F @ 2500 PSIG /148°C @ 172 BAR
<b>Orifice</b>	0.187 in /4.7 mm
<b>Packing</b>	Modified PTFE
<b>Ring/Disc Material</b>	Stainless Steel
<b>Room Temperature Pressure Rating</b>	2500 PSIG @ 100°F /172 BAR @ 37°C
<b>Testing</b>	Testing according to WS-22
<b>UNSPSC (10.0)</b>	40141607
<b>UNSPSC (11.0501)</b>	40141607
<b>UNSPSC (13.0601)</b>	40141607
<b>UNSPSC (15.1)</b>	40141607
<b>UNSPSC (4.03)</b>	40141607

**UNSPSC (SWG01)**

40141607

**Valve Material**

Stainless Steel

 The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

 Caution: Do not mix or interchange valve components with those of other manufacturers.